



ورقة البيانات الفنية

اسم المنتج: معجونة ناعمة ممتازة

الوصف:

معجونة مائية اكسترا ذات اساس P.V.A تستخدم من اجل اغلاق الشقوق والحفر وتسوية الاسطح الاسمنتية قبل الطلاءات النهائية

المواصفات الفيزيائية:

- الكثافة: ١,٨٠ كغ/ل
- المحتوى الصلب: ٧٤٪
- اللون: ابيض
- درجة الحموضة: ٧,٥
- المركبات العضوية المتطايرة: خالي من المركبات العضوية المتطايرة (≥ 1000 جزء من المليون)

التعبئة:

- يعبأ في عبوات بلاستيكية عاتمة محكمة الاغلاق

الوزن القائم	العبوة
٢٠ كغ	١٦ ل
٦ كغ	٤ ل

التخزين:

- يحفظ المنتج في مكان بارد وجاف (درجة حرارة ٢٠س) ويمنع تعرضه لأشعة الشمس المباشرة

Al Jameel International Establishment

For the manufacture of paints and insulating coatings

00963152215226

info@algmeal.com

www.algmeal.com



Technical Data Sheet

Product name: **Excellent soft Putty**

the description:

P.V.A Extra Water-based Putty is used for sealing cracks and pits and leveling cement surfaces before final coatings.

Physical Specifications:

- **Density:** 1.80 kg/L
- **Solid content:** 74%
- **pH:** 7.5
- **color:** white
- **VOC:** No VOC (≤ 1500 ppm)

packing:

Packaged in opaque, airtight plastic containers

Packaging	gross weight
14 L	20Kg
4 L	6 Kg

Storage:

- Store the product in a cool and dry place (20°C) and prevent exposure to direct sunlight

Al Jameel International Establishment

For the manufacture of paints and insulating coatings

00963152215226

info@algmeal.com

www.algmeal.com